
Etikettier-Station
K 81 T



Etikettierstation mit Spender, Drucker und Förderband



Etikettierstation „oben/unten“: Produktober- und -unterseite etikettieren in einem Arbeitsgang, wahlweise mit unterschiedlichen Etikettierern.

Die Kombination von Etikettenspender, Thermo-Druckerwerk und Transportband ist das Besondere an der Etikettier-Station **K 81 T**. Die Anlage kann damit in vielfältiger Weise auch in vorhandene Verpackungslinien eingefügt werden.

Es wird komplettiert durch die Etiketten-Gestaltungssoftware Labelstar Office LITE, die neben Text auch Grafik und Bar-Codes erstellen kann. Die Übertragung des Etiketten-Layouts vom PC an das Drucksystem kann wahlweise über LAN-Kabel, USB-Kabel, CF Speicherkarte oder USB-Stick erfolgen.

Der Etikettenspender wird als links und als rechts laufende Version angeboten. Etikettierer und Transportband sind höhenverstellbar.

Die Laufgeschwindigkeit des Transportbandes ist stufenlos regelbar. Der Fördergurt ist für Lebensmittel geeignet.

Etikettenabtastung und Produkt-Erkennung über Lichtschranken.

Technische Daten:

Max. Etikettendruckbreite:	81 mm
Max. Durchlassbreite:	90 mm
Etikettenrolldurchmesser:	360 mm
Max. Druckgeschwindigkeit:	300 mm/sec
Drucker-Type:	Thermotransfer
Schnittstellen:	Seriell, Parallel, USB, LAN, CF-Karte
Schrifthöhe:	1 mm - 99 mm
Druck (s/w):	zahlreiche Fonts, Barcodes, Grafik
Transportband:	200 mm breit 1200 mm lang
Höhenverstellbar:	750 mm - 950 mm
Netzanschluss:	230 V/ 50 Hz
Gewicht ca.	100 kg

kreBeck Stalleinrichtungen & Apparatebau
Konzepte voller Ideen


A. Krebeck - Stalleinrichtungen und Apparatebau GmbH
Osterdammer Str. 34 49401 Damme
Tel.: 05491/9667-0 Fax: 05491/9667-50
info@krebeck.com krebeck.com

Technische Änderungen vorbehalten 11.16

Labelling Station
K 81 T



Labelling station with dispenser, printer and conveyor



Labelling station to apply labels on top and on bottom, in one processing step, optionally with different types of labeler.

Technical Details:

Max. print width:	81 mm
Max. label width:	90 mm
Label reel diameter:	360 mm
Max. print speed:	300 mm/sec
Printer Type:	Thermotransfer
Interfaces:	seriell, parallel, USB, LAN,CF-Memory card
Print hight:	1 mm - 99 mm
Print (b/w):	numerous fonts, barcodes, graphics
Conveyor:	200 mm width 1200 mm length
Height adjustable:	750 mm - 950 mm
Voltage:	230 V/ 50 Hz
Weight ca.	100 kg

The combination of label dispenser, thermoprinter and conveyor in one unit is the distinctive feature of the labelling station **K 81 T**. With this, the station can be well integrated in existing packaging lines in a variety of ways.

It is completed with a label layout software called Labelstar Office LITE, which in addition to plain text handles graphics and bar codes. The link between PC and printer can be LAN cable, USB cable or CF memory card, USB stick.

The labelling station can be mounted both as a clockwise and as a counterclockwise running version.

Labeler and conveyor are height adjustable. The speed of the conveyor belt is steplessly variable, the belt made of food save material.

Label sampling and product recognition are based on photo sensor technique.

krebeck Stalleinrichtungen & Apparatebau
Konzepte voller Ideen

A. Krebeck - Stalleinrichtungen und Apparatebau GmbH
Osterdammer Str. 34 49401 Damme
Tel.: 05491/9667-0 Fax: 05491/9667-50
info@krebeck.com krebeck.com

Subject to technical changes 11.16