



The ADS 200/4 linear system features four powerful dosing arms for highly efficient processing of berries and bulk materials.

The product is distributed completely evenly to the individual dosing arms via a modern transverse distribution plate.

Via four precise dosing belts, the goods are gently conveyed into the respective weighing drums, where the exact weighing process takes place.

A product-friendly rotary valve discharges the precisely weighed berries directly into the punnets, which are fed via a cross-running punnet conveyor. Due to the constant filling height of the punnets and the compact design, large drop heights are reliably avoided. The weighing process and punnet feed take place simultaneously

Main features

- Punnet conveyor length: approx. 3000 mm
- Constant filling height of the punnets
- Individual width adjustment from 50 mm to 180 mm easily adjustable via handwheel
- Suitable for punnets (max. 1 kg filling weight), clamshells and cups

Technical specification

- Throughput: max. 60 punnets / min.*
- Infeed height: approx. 1370 mm
- Integrated remote maintenance via Internet
- Control system for inspection belt and feeding belt
- Hopper full level sensor as standard
- Power supply: 230 Volt

*depending on filling weight, fine adjustment and feed quantity.

krebeck Stalleinrichtungen & Apparatebau
Konzepte voller Ideen

A. Krebeck - Stalleinrichtungen und Apparatebau GmbH
Osterdammer Str. 34 49401 Damme
Tel.: 05491/9667-0 Fax: 05491/9667-50
info@krebeck.com krebeck.com

Technische Änderungen vorbehalten 10.26