

Weighing line 4-head



The compact weighing line features 1 x 4 highly efficient weighing systems, each equipped with its own weighing belt and a separate weight indicator.

This enables a single operator to precisely check up to 4 punnets at the same time and make manual corrections by quickly adding or removing products.

The punnets are fed fully automatically to the four weighing belts via an integrated infeed conveyor.

As soon as a weighing platform becomes available, the next punnet is automatically pushed forward. Once the target weight is reached, the punnets are smoothly transferred to the outfeed conveyor. The traffic-light-style LED display (red-yellow-green-yellow-red) consisting of 16 color LEDs each allows for lightning-fast check processes out of the corner of the eye.

Main features

- Punnet clearance width: 200 mm
- Integrated infeed conveyor for precise punnet transfer
- 4 weighing belts including LED traffic-light displays
- Outfeed conveyor with stable product forwarding
- Including software & remote maintenance via Internet

Technical specification

- Dimensions (L x W x H): 2759 x 449 x 867 mm
- Control unit: Modern KCP 7" touch terminal
- Control cabinet with precise frequency regulation
- Housing completely made of durable stainless steel
- Belts absolutely suitable for food products
- Power supply: 230 V / Custom dimensions on request

krebeck Stalleinrichtungen & Apparatebau
Konzepte voller Ideen

A. Krebeck - Stalleinrichtungen und Apparatebau GmbH
Osterdammer Str. 34 49401 Damme
Tel.: 05491/9667-0 Fax: 05491/9667-50
info@krebeck.com krebeck.com

10.26